



355°Horizontally


90°Tilt



WH BK SV

Cyclops

- Aluminum material in powder coating.
- 3 phase track and 1 phase track adaptor are available.



18°



22°




40°




66°

TRIAC LED IP20 RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
19044-112O	11W	WL 2700K	66°	918 lm
19044-113O	11W	WL 3000K	66°	947 lm
19044-114O	11W	NL 4000K	66°	1041 lm
19044-11CO	11W	CL 5700K	66°	1145 lm

DALI TRIAC LED IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
19047-142S	14W	WL 2700K	18°	1299 lm
19047-142L	14W	WL 2700K	40°	1192 lm
19047-143S	14W	WL 3000K	18°	1340 lm
19047-143L	14W	WL 3000K	40°	1229 lm
19047-144S	14W	NL 4000K	18°	1474 lm
19047-144L	14W	NL 4000K	40°	1352 lm
19047-14CS	14W	CL 5700K	18°	1474 lm
19047-14CL	14W	CL 5700K	40°	1352 lm
19047-192S	19W	WL 2700K	18°	1816 lm
19047-192L	19W	WL 2700K	40°	1813 lm
19047-193S	19W	WL 3000K	18°	1935 lm
19047-193L	19W	WL 3000K	40°	1870 lm
19047-194S	19W	NL 4000K	18°	2128 lm
19047-194L	19W	NL 4000K	40°	2057 lm
19047-19CS	19W	CL 5700K	18°	2341 lm
19047-19CL	19W	CL 5700K	40°	2252 lm