



WH BK SV

# Gimbo

- Aluminum die casting with electrostatic powder coating, 355 degree rotate, 40 degree tilt.
- Nice design with handler for ease of pull. Removing the front ring to replace the filter and accessories, various selected beam from spot to flood.



15°



24°




40°




58°

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
8451-092M	9W	WL 2700K	24°	818 lm
8451-092L	9W	WL 2700K	40°	824 lm
8451-092W	9W	WL 2700K	58°	690 lm
8451-093M	9W	WL 3000K	24°	880 lm
8451-093L	9W	WL 3000K	40°	850 lm
8451-093W	9W	WL 3000K	58°	712 lm
8451-094M	9W	NL 4000K	24°	968 lm
8451-094L	9W	NL 4000K	40°	935 lm
8451-094W	9W	NL 4000K	58°	783 lm
8451-09CM	9W	CL 5700K	24°	1056 lm
8451-09CL	9W	CL 5700K	40°	1020 lm
8451-09CW	9W	CL 5700K	58°	854 lm

DALI TRIAC LED IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
8452-182S	18W	WL 2700K	14°	2091 lm
8452-182M	18W	WL 2700K	20°	2020 lm
8452-182L	18W	WL 2700K	40°	1860 lm
8452-182W	18W	WL 2700K	58°	1841 lm
8452-183S	18W	WL 3000K	14°	2156 lm
8452-183M	18W	WL 3000K	20°	2082 lm
8452-183L	18W	WL 3000K	40°	1918 lm
8452-183W	18W	WL 3000K	58°	1898 lm
8452-184S	18W	NL 4000K	14°	2372 lm
8452-184M	18W	NL 4000K	20°	2290 lm
8452-184L	18W	NL 4000K	40°	2110 lm
8452-184W	18W	NL 4000K	58°	2088 lm
8452-18CS	18W	CL 5700K	14°	2587 lm
8452-18CM	18W	CL 5700K	20°	2498 lm
8452-18CL	18W	CL 5700K	40°	2302 lm
8452-18CW	18W	CL 5700K	58°	2278 lm

DALI TRIAC LED IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
8453-282S	28W	WL 2700K	20°	2681 lm
8453-282L	28W	WL 2700K	36°	2730 lm
8453-282W	28W	WL 2700K	60°	2568 lm
8453-283S	28W	WL 3000K	20°	2764 lm
8453-283L	28W	WL 3000K	36°	2814 lm
8453-283W	28W	WL 3000K	60°	2647 lm
8453-284S	28W	NL 4000K	20°	3040 lm
8453-284L	28W	NL 4000K	36°	3095 lm
8453-284W	28W	NL 4000K	60°	2912 lm
8453-28CS	28W	CL 5700K	20°	3317 lm
8453-28CL	28W	CL 5700K	36°	3377 lm
8453-28CW	28W	CL 5700K	60°	3176 lm