

# Holo pro

DALI

TRIAC


LED

IP20

0-10V

RA>80

RA>90




CODE	Watts	CCT	Beam	Lumen
2196-072S	7W	WL 2700K	16°	423 lm
2196-072M	7W	WL 2700K	26°	405 lm
2196-073S	7W	WL 3000K	16°	436 lm
2196-073M	7W	WL 3000K	26°	418 lm
2196-074S	7W	NL 4000K	16°	480 lm
2196-074M	7W	NL 4000K	26°	446 lm
2196-092S	9W	WL 2700K	16°	510 lm
2196-092M	9W	WL 2700K	26°	481 lm
2196-093S	9W	WL 3000K	16°	526 lm
2196-093M	9W	WL 3000K	26°	496 lm
2196-094S	9W	NL 4000K	16°	578 lm
2196-094M	9W	NL 4000K	26°	546 lm

TRIAC

GX5.3

IP20




CODE	Watts
2096M	50W max

TRIAC


GU10

IP20




CODE	Watts
2096G	50W max

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
2198-072S	7W	WL 2700K	16°	324 lm
2198-072M	7W	WL 2700K	26°	318 lm
2198-073S	7W	WL 3000K	16°	334 lm
2198-073M	7W	WL 3000K	26°	328 lm
2198-074S	7W	NL 4000K	16°	367 lm
2198-074M	7W	NL 4000K	26°	360 lm
2198-092S	9W	WL 2700K	16°	387 lm
2198-092M	9W	WL 2700K	26°	380 lm
2198-093S	9W	WL 3000K	16°	399 lm
2198-093M	9W	WL 3000K	26°	392 lm
2198-094S	9W	NL 4000K	16°	439 lm
2198-094M	9W	NL 4000K	26°	431 lm

TRIAC GX5.3 IP20



CODE	Watts
2198M	50W max

TRIAC GU10 IP20



CODE	Watts
2198G	50W max