




WH BK SV

## Holo series overview

- Universal fixture designed in LED module, Gx5.3 MR16 and GU10 QPAR16, Up and down ceiling support is locked by screw driver, Good for soft ceiling, 15 kinds of diffuser in option, trimless design with ceiling ring.
- Metal sheet with electrostatic powder coating, Very thin trim 1 mm only, Oval hole with 30 degree tilt on light source, Black color on core without light leak.
- Aluminum die casting material. The removable core to replace the light source without damage to the ceiling, various selections on LED module, Gx5.3 MR16 and GU10, QPAR16.


# Holo

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
2091U-072S	7W	● WL 2700K	18°	771 lm
2091U-072L	7W	● WL 2700K	36°	747 lm
2091U-073S	7W	● WL 3000K	18°	795 lm
2091U-073L	7W	● WL 3000K	36°	770 lm
2091U-074S	7W	● NL 4000K	18°	875 lm
2091U-074L	7W	● NL 4000K	36°	847 lm
2091U-092S	9W	● WL 2700K	18°	943 lm
2091U-092L	9W	● WL 2700K	36°	917 lm
2091U-093S	9W	● WL 3000K	18°	972 lm
2091U-093L	9W	● WL 3000K	36°	945 lm
2091U-094S	9W	● NL 4000K	18°	1070 lm
2091U-094L	9W	● NL 4000K	36°	1040 lm

TRIAC GX5.3 IP20




CODE	Watts
2091M	50W max

TRIAC GU10 IP20




CODE	Watts
2091G	50W max

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
2091SU-072S	7W	WL 2700K	18°	771 lm
2091SU-072L	7W	WL 2700K	36°	747 lm
2091SU-073S	7W	WL 3000K	18°	795 lm
2091SU-073L	7W	WL 3000K	36°	770 lm
2091SU-074S	7W	NL 4000K	18°	875 lm
2091SU-074L	7W	NL 4000K	36°	847 lm
2091SU-092S	9W	WL 2700K	18°	943 lm
2091SU-092L	9W	WL 2700K	36°	917 lm
2091SU-093S	9W	WL 3000K	18°	972 lm
2091SU-093L	9W	WL 3000K	36°	945 lm
2091SU-094S	9W	NL 4000K	18°	1070 lm
2091SU-094L	9W	NL 4000K	36°	1040 lm

TRIAC GX5.3 IP20




CODE	Watts
2091SM	50W max

TRIAC GU10 IP20




CODE	Watts
2092SG	50W max

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
2097U-072S	7W	WL 2700K	18°	778 lm
2097U-072L	7W	WL 2700K	36°	736 lm
2097U-073S	7W	WL 3000K	18°	802 lm
2097U-073L	7W	WL 3000K	36°	759 lm
2097U-074S	7W	NL 4000K	18°	881 lm
2097U-074L	7W	NL 4000K	36°	835 lm
2097U-092S	9W	WL 2700K	18°	920 lm
2097U-092L	9W	WL 2700K	36°	892 lm
2097U-093S	9W	WL 3000K	18°	948 lm
2097U-093L	9W	WL 3000K	36°	920 lm
2097U-094S	9W	NL 4000K	18°	1043 lm
2097U-094L	9W	NL 4000K	36°	1012 lm

TRIAC GX5.3 IP20



CODE	Watts
20971M	50W max

TRIAC GU10 IP20



CODE	Watts
20972G	50W max