

WH BK

In-tech

- Aluminum die casting with powder coating.
- 99.8% pure aluminum reflector.
- Optional accessories available.
- Various light sources in LED module and Gx5.3 MR16.




20°




36°

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
2175-072S	7W	WL 2700K	19°	745 lm
2175-072L	7W	WL 2700K	35°	728 lm
2175-073S	7W	WL 3000K	19°	768 lm
2175-073L	7W	WL 3000K	35°	750 lm
2175-074S	7W	NL 4000K	19°	845 lm
2175-074L	7W	NL 4000K	35°	826 lm
2175-092S	9W	WL 2700K	19°	880 lm
2175-092L	9W	WL 2700K	35°	866 lm
2175-093S	9W	WL 3000K	19°	907 lm
2175-093L	9W	WL 3000K	35°	893 lm
2175-094S	9W	NL 4000K	19°	998 lm
2175-094L	9W	NL 4000K	35°	982 lm
2175-132S	13W	WL 2700K	19°	1028 lm
2175-132L	13W	WL 2700K	35°	995 lm
2175-133S	13W	WL 3000K	19°	1060 lm
2175-133L	13W	WL 3000K	35°	1026 lm
2175-134S	13W	NL 4000K	19°	1167 lm
2175-134L	13W	NL 4000K	35°	1129 lm

TRIAC Gx5.3 IP20




CODE	Watts
21754	50W max

DALI TRIAC LED IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
2175T-072S	7W	WL 2700K	19°	745 lm
2175T-072L	7W	WL 2700K	35°	728 lm
2175T-073S	7W	WL 3000K	19°	768 lm
2175T-073L	7W	WL 3000K	35°	750 lm
2175T-074S	7W	NL 4000K	19°	845 lm
2175T-074L	7W	NL 4000K	35°	826 lm
2175T-092S	9W	WL 2700K	19°	880 lm
2175T-092L	9W	WL 2700K	35°	866 lm
2175T-093S	9W	WL 3000K	19°	907 lm
2175T-093L	9W	WL 3000K	35°	893 lm
2175T-094S	9W	NL 4000K	19°	998 lm
2175T-094L	9W	NL 4000K	35°	982 lm
2175T-132S	13W	WL 2700K	19°	1028 lm
2175T-132L	13W	WL 2700K	35°	995 lm
2175T-133S	13W	WL 3000K	19°	1060 lm
2175T-133L	13W	WL 3000K	35°	1026 lm
2175T-134S	13W	NL 4000K	19°	1167 lm
2175T-134L	13W	NL 4000K	35°	1129 lm

TRIAC Gx5.3 IP20



CODE	Watts
21754T	50W max