



WH BK SV

Marco mini

- Universal fixture designed in LED module, GX5.3 MR16 and GU10 GPAR16.
- Up and down Ceiling support is locked by screw driver, good for soft ceiling, 15 kinds of diffuser in option.
- Trimless design with ceiling ring.




18°




36°

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
9320-082S	8W	WL 2700K	18°	697 lm
9320-082L	8W	WL 2700K	36°	692 lm
9320-083S	8W	WL 3000K	18°	719 lm
9320-083L	8W	WL 3000K	36°	693 lm
9320-084S	8W	NL 4000K	18°	791 lm
9320-084L	8W	NL 4000K	36°	762 lm
9320-102S	10W	WL 2700K	18°	839 lm
9320-102L	10W	WL 2700K	36°	807 lm
9320-103S	10W	WL 3000K	18°	865 lm
9320-103L	10W	WL 3000K	36°	832 lm
9320-104S	10W	NL 4000K	18°	951 lm
9320-104L	10W	NL 4000K	36°	915 lm

TRIAC GX5.3 IP20




CODE	Watts
93201	50W max

TRIAC GU10 IP20




CODE	Watts
93202	50W max

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
9320T-082S	8W	WL 2700K	18°	697 lm
9320T-082L	8W	WL 2700K	36°	692 lm
9320T-083S	8W	WL 3000K	18°	719 lm
9320T-083L	8W	WL 3000K	36°	693 lm
9320T-084S	8W	NL 4000K	18°	791 lm
9320T-084L	8W	NL 4000K	36°	762 lm
9320T-102S	10W	WL 2700K	18°	839 lm
9320T-102L	10W	WL 2700K	36°	807 lm
9320T-103S	10W	WL 3000K	18°	865 lm
9320T-103L	10W	WL 3000K	36°	832 lm
9320T-104S	10W	NL 4000K	18°	951 lm
9320T-104L	10W	NL 4000K	36°	915 lm

TRIAC Gx5.3 IP20



CODE	Watts
93201T	50W max

TRIAC GU10 IP20



CODE	Watts
93202T	50W max