



WH BK SV

## Petit

- Aluminum die casting material with electrostatic powder coating.
- Small aperture design in pin hole and oval hole for task lighting, 30 degree tilt.
- Various light sources selected in Integrated LED / LED module.




16°




28°

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
2173-072S	7W	WL 2700K	16°	436 lm
2173-072M	7W	WL 2700K	28°	338 lm
2173-073S	7W	WL 3000K	16°	450 lm
2173-073M	7W	WL 3000K	28°	349 lm
2173-074S	7W	NL 4000K	16°	495 lm
2173-074M	7W	NL 4000K	28°	383 lm
2173-092S	9W	WL 2700K	16°	487 lm
2173-092M	9W	WL 2700K	28°	376 lm
2173-093S	9W	WL 3000K	16°	503 lm
2173-093M	9W	WL 3000K	28°	388 lm
2173-094S	9W	NL 4000K	16°	553 lm
2173-094M	9W	NL 4000K	28°	426 lm

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
2174-152S	15W	WL 2700K	16°	766 lm
2174-152M	15W	WL 2700K	28°	652 lm
2174-153S	15W	WL 3000K	16°	784 lm
2174-153M	15W	WL 3000K	28°	673 lm
2174-154S	15W	WL 4000K	16°	862 lm
2174-154M	15W	WL 4000K	28°	740 lm

TRIAC Gx5.3 IP20




**CODE**

**Watts**

21721

50W max



TRIAC Gx5.3 IP20




**CODE**

**Watts**

21722

50W max



TRIAC Gx5.3 IP20



**CODE**

**Watts**

21723

50W max

