



WH BK SV

## Proset

- Aluminum die casting with electrostatic powder coating.
- 99.8% aluminum reflector with excellent light distribution.
- Deep reflector design without light glaring excellent for general lighting.
- Option in DC with high quality driver premium occasion or AC less flickering for Eco usage.



46°



62°




70°

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
82561-1230	12W	WL 3000K	70°	1131 lm
82561-1240	12W	NL 4000K	70°	1244 lm

TRIAC LED IP44 IP20 RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
82562-1530	15W	WL 3000K	70°	1005 lm
82562-1540	15W	NL 4000K	70°	1105 lm

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
82571-203W	20W	WL 3000K	60°	1783 lm
82571-204W	20W	NL 4000K	60°	1961 lm

TRIAC LED IP44 IP20 RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
82572-203W	20W	WL 3000K	60°	1436 lm
82572-204W	20W	NL 4000K	60°	1579 lm

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
82561-1230	12W	WL 3000K	70°	1131 lm
82561-1240	12W	NL 4000K	70°	1244 lm

TRIAC LED IP44 IP20 RA>80 RA>90

CODE	Watts	CCT	Beam	Lumen
82581-263F	26W	WL 3000K	46°	2020 lm
82581-264F	26W	NL 4000K	46°	2222 lm