



WH BK SV

Sunray

- Aluminum die casting with electrostatic powder coating.
- 99.8% aluminum reflector, Uniform Light.
- Black baffle for, anti - glare, frost glass, central frost and clear glass in option.
- Easy Installation and no damage to soft ceiling.
- 20253 / 20264 designed with dimmable and tunable function for deluxe retail business and high level hospitality.
- Triac / 0-10V / DALI function is in option.




60°



44°

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
20255-103W	10W	WL 3000K	60°	825 lm
20255-104W	10W	NL 4000K	60°	907 lm

DIM+TUNE LED IP44 IP20 RA>80 RA>90

CODE	Watts	CCT	Beam	Lumen
20253-080W	8W	C 2700K-6500K	60°	640-700 lm

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
20263-133F	13W	WL 3000K	46°	1115 lm
20263-134F	13W	NL 4000K	46°	1226 lm
20265-193L	19W	WL 3000K	40°	1433 lm
20265-194L	19W	NL 4000K	40°	1576 lm

DIM+TUNE LED IP44 IP20 RA>80 RA>90

CODE	Watts	CCT	Beam	Lumen
20253-080W	20W	C 2700K-6500K	40°	1800-2000 lm

DALI

TRIAC

LED


IP44

IP20

0-10V

RA>
80

RA>
90



CODE	Watts	CCT	Beam	Lumen
20273-273F	27W	WL 3000K	48°	2367 lm
20273-274F	27W	NL 4000K	48°	2603 lm
20275-403F	40W	WL 3000K	44°	3462 lm
20275-404F	40W	NL 4000K	44°	3808 lm