



WH BK SV

## Vertex

- Aluminum die casting with electrostatic powder coating for durability.
- Very low profile design less 100mm height especially for limited space.
- Deep baffle free of light glaring.
- Fine design 99.8% aluminum reflector with excellent light distribution.
- Easy installation and no damage to soft ceiling.
- 20553 / 20564 designed with dimmable and tunable function for deluxe retail business and high level hospitality.
- Triac / 0-10V / DALI function is in option.




42°



50°

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
20555-103F	10W	WL 3000K	47°	740 lm
20555-104F	10W	NL 4000K	47°	814 lm

DIM+TUNE LED IP44 IP20 RA>80 RA>90

CODE	Watts	CCT	Beam	Lumen
20553-080F	8W	C 2700K-6500K	47°	640-700 lm

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
20563-133F	13W	WL 3000K	42°	1081 lm
20563-134F	13W	NL 4000K	42°	1134 lm
20565-193F	19W	WL 3000K	42°	1438 lm
20565-194F	19W	NL 4000K	42°	1582 lm

DIM+TUNE LED IP44 IP20 RA>80 RA>90

CODE	Watts	CCT	Beam	Lumen
20564-200F	20W	C 2700K-6500K	42°	1800-2000 lm

DALI TRIAC LED IP44 IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
20573-273F	27W	WL 3000K	44°	2710 lm
20573-274F	27W	NL 4000K	44°	2981 lm
20575-393F	39W	WL 3000K	50°	3824 lm
20575-394F	39W	NL 4000K	50°	4206 lm