



WH BK

Wedge

- Surface mounting designed in trimless without frame, small size with 10w LED light source and large size with 20w LED light source.
- Free direction and 30 degree tilt, by removing front ring designed to install accessories easily. Medium to wide flood optics are available.




18°




40°

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
W4301-103S	10W	WL 3000K	17°	869 lm
W4301-103L	10W	WL 3000K	36°	850 lm
W4301-104S	10W	NL 4000K	17°	955 lm
W4301-104L	10W	NL 4000K	36°	935 lm

DALI TRIAC LED IP20 0-10V RA>80 RA>90




CODE	Watts	CCT	Beam	Lumen
W4302-203S	10W * 2	WL 3000K	18°	1646 lm
W4302-203L	10W * 2	WL 3000K	37°	1685 lm
W4302-204S	10W * 2	NL 4000K	18°	1810 lm
W4302-204L	10W * 2	NL 4000K	37°	1853 lm

DALI TRIAC LED IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
W4311-203M	20W	WL 3000K	21°	1919 lm
W4311-203L	20W	WL 3000K	39°	1856 lm
W4311-204M	20W	NL 4000K	21°	2110 lm
W4311-204L	20W	NL 4000K	39°	2041 lm

DALI TRIAC LED IP20 0-10V RA>80 RA>90



CODE	Watts	CCT	Beam	Lumen
W4312-403M	20W * 2	WL 3000K	21°	3656 lm
W4312-403L	20W * 2	WL 3000K	38°	3618 lm
W4312-404M	20W * 2	NL 4000K	21°	4031 lm
W4312-404L	20W * 2	NL 4000K	38°	3979 lm